

Application No. 10/736,503
Amendment dated November 14, 2005
Reply to Office Action of October 17, 2005

Page 2

The claims of the application have been amended as follows:

1. (canceled)

2. (currently amended) ~~An induction sensor as claimed in claim 1~~ A bank validator as claimed in claim 27 wherein said sensing element of each induction sensor is adjacent an edge of said sensor and includes first and second overlapping elongate conductor portions connected in series and defining a measuring gap therebetween which is sensitive to changes in inductance and capacitance which occur adjacent said edge.

3. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 2 wherein said sensing element of each induction sensor is part of said printed circuit.

4. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 3 wherein said first elongate conductor portions of each induction sensor is provided on one layer of said printed circuit and said second elongate conductor portions is provided on a different layer of said printed circuit.

5. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 4 wherein said secondary coil of each induction sensor is a one turn coil.

6. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 5 wherein said one turn of said secondary coil of each induction sensor is of a wide width to generally overlap with said primary coil.

7. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 1-27 wherein said ~~sensor~~ sensing element of

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 3

each induction sensor includes two primary coils located in different layers of said printed circuit.

8. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 7 wherein said primary coils of each induction sensor are separated by the layer containing said secondary coil.

9. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 1-27 wherein said sensing element of each induction sensor is defined by external conductors connected to said secondary coil.

10. (currently amended) ~~An induction sensor~~ A banknote validator as claimed in claim 1-27 in combination with a second induction sensor of the same structure and wherein said sensors are provided in a common printed circuit.

11. (currently amended) A banknote validator comprising a banknote evaluation channel, a transport arrangement for moving a banknote through said evaluation channel, at least one induction sensor placed in one side of said evaluation channel for sensing changes of the magnetic and inductive properties of a banknote as it is moved past said at least one induction sensor wherein said induction sensor comprises ~~A planar induction sensor for sensing magnetic and conductive security structures, said planar induction sensor comprising~~ a multilayered printed circuit having a current transformer and an operating coil, said current transformer comprising a planar spiral-type primary coil provided on one layer of said printed circuit with an associated secondary coil in an adjacent layer of the printed circuit board, said primary coil cooperating with said secondary coil to induce a responsive intensive current in said secondary coil, said secondary coil being connected to the operating coil, said operating coil forming a testing magnetic field responsive to

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 4

changes in magnetic and conductive properties of ~~security-structure~~ a banknote when moved past said operating coil.

12. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer and operating coil are situated on the same multilayer printed circuit board and the operating coil is formed by the printed conductors on of said multilayer printed circuit board.

13. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer contains one primary coil and one secondary coil situated on adjacent layers of the multilayer printed board.

14. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer comprises two series primary coils in different layers of said circuit board separated by a layer containing said secondary coil of current transformer.

15. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer comprises two connected in parallel primary coils in different layers of said printed circuit separated by the layer containing said secondary.

16. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer has a primary coil with a constant width of turns and constant distance between the turns.

17. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer

Application No. 10/736,503
Amendment dated November 14, 2005

~~Reply to Office Action of October 17, 2005~~

Page 5

has a primary coil with a constant width of turns and a variable distance between the turns, said distance increasing with increasing of the length of said turns.

18. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said current transformer has a primary coil with a constant distance between turns and a variable width of the turns, said width increasing with increasing of the length of said turns.

19. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein said operating coil contains two or more wires with different directions of currents.

20. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein one point of said operating coil is connected to one end of the primary coil of the current transformer.

21. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 11 wherein ~~said~~ each induction sensor contains several current transformers, each being connected to an individual operating coil.

22. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim 1-27 ~~including associated with planar induction sensor~~ wherein each induction sensor includes associated electronic processing circuitry mounted on the multilayered printed circuit board ~~of said planar induction sensor~~.

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 6

23. (currently amended) ~~The planar induction sensor~~ A banknote validator as claimed in claim ~~1- 27~~ wherein several ~~planar~~ induction sensors with ~~and~~ associated electronic circuits are incorporated on ~~different places of the one~~ printed circuit board.

24. (canceled)

25. (canceled)

26. (canceled)

27. (currently amended) A banknote validator comprising a banknote evaluation channel, a transport arrangement for moving a banknote through said evaluation channel, at least one induction sensor placed in one side of said evaluation channel for sensing changes of the magnetic and inductive properties of a banknote as it is moved past said at least one induction sensor; ~~said at least one~~ wherein each induction sensor ~~comprising~~ comprises a multi layered printed circuit and a sensing element, said printed circuit including a first layer having a primary coil thereon and a second layer having a secondary coil thereon, said primary coil being located in overlapping relation with said secondary coil to induce a responsive current in said secondary coil, said sensing element being electrically connected with said secondary coil to form a closed loop therewith, said sensing element concentrating the responsive current of said secondary coil and rendering the sensing element responsive to changes in inductance and conductivity caused by changes in magnetic or inductive properties of a banknote as it is moved past said sensing element.

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

~~Page 7~~

28. (original) A banknote validator as claimed in claim 27 having at least two induction sensors with one induction sensor located on one side of the banknote evaluation channel and said second induction sensor located on the opposite side of the evaluation channel.

29. (original) A banknote validator as claimed in claim 28 wherein each of said induction sensors have separate electronic circuitry for processing the signals thereof.

30. (currently amended) ~~A~~ In a banknote validator, a planar induction sensor for sensing magnetic and conductive security structures as processed by the banknote validator, said planar induction sensor comprising planar current transformers manufactured by multilayer printed circuit board technology and operating coils, said current transformers comprising planar spiral-type primary coils associated with a planar secondary coils in the nearest layers of the printed circuit board, said primary coils induce a responsive intensive current in said secondary coils, said secondary coils being connected to the operating coils, said operating coils forming a testing magnetic field on the magnetic and conductive security structures.

31. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformers are manufactured by multilayer printed circuit board technology and said operating coils are formed by external wires.

32. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformers and operating coils are situated on the same multilayer printed circuit board and the operating coils are

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 8

formed by the printed wires of said multilayer printed circuit board.

33. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer contains one primary coil and one secondary coil being situated in nearest layers of the multilayer printed board.

34. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises two series primary coils in different layers, separated by the layers in which the secondary coil of current transformer are located.

35. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises two conducted in parallel primary coils in different layers, separated by the layers in which the secondary coils of the current transformer are situated.

36. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises more than two conducted in serial primary coils in different layers, separated by the layers in which the secondary coils of the current transformer are situated.

37. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 4-30 wherein said current transformer comprises more then two conducted in serial-parallel primary coils in different layers, separated by the layers in which the secondary coils of the current transformer are situated.

Application No. 10/736,503
Amendment dated November 14, 2005
Reply to Office Action of October 17, 2005

Page 9

37. (canceled)

38. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises two or more primary coils with individual exit pins.

39. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer ~~comprises~~ includes one-turn secondary coil in one layer of said printed circuit board.

40. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer ~~comprises~~ includes two or more turns of secondary coil in one layer of said printed circuit board.

41. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises two conducted in serial secondary coils in different layers, separated by the layers in which the primary coils of the current transformer are situated.

42. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises two conducted in parallel secondary coils in different layers, separated by the layers in which the primary coils of the current transformer are situated.

43. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer comprises more than two secondary coils in the different layers

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 10

conducted in serial-parallel and separated by the layers in which the primary coils of the current transformer are situated.

44. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer has a primary coil with a constant width of turns and constant distance between the turns.

45. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer has a primary coil with a constant width of turns and a variable distance between the turns, said distance increasing as the length of said turns increases.

46. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said current transformer has a primary coil with a constant distance between turns and a variable width of the turns, said width increasing as the length of said turns increases.

47. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said operating coil contains one wire.

48. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said operating coil contains several wires where currents flow in the same direction.

49. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said operating coil contains two or more wires with different directions of currents.

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 11

50. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein one point of said operating coil is connected to one end of the primary coil of the current transformer.

51. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein one point of said operating coil is connected to one end of the primary coil of the current transformer through the capacitor.

52. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein said induction sensor contains several current transformers, each being connected to an individual operating coil.

53. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein associated with planar induction sensor electronic processing circuitry is mounted on the multilayer printed circuit board of said planar induction sensor.

54. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein several planar induction sensors are incorporated in different locations on one printed circuit board.

55. (currently amended) ~~The planar induction sensor~~ In a banknote validator as claimed in claim 30 wherein several planar induction sensors with associated electronic circuits are incorporated on one printed circuit board.

56. (canceled)

Application No. 10/736,503

Amendment dated November 14, 2005

Reply to Office Action of October 17, 2005

Page 12

57. (canceled)

58. (canceled)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.